

### DATA SHEET

# LED EMERGENCY BULKHEAD GUARD





#### **Product Features**

- 3 hours Emergency Bulkhead
- 3W, 150lm
- Class II protection
- IP65 and IK06
- Hinged gear tray with push fit terminals
- Maintained or Non-maintained type
- Wall/Ceiling Mount Installation can be recessed mounted with help of a mounting kit.
- Battery type: Ni-Cd 3.6V 1500mAh



## **General Specifications**

	BULKHEAD GUARD 3W 3H IP65			
	Wattage	3W		
Electrical Data	Voltage range	220 - 240VAC		
	Power factor	0.5		
	Input current(max)	30mA		
	Line frequency	50/60Hz		
	Surge Voltage capability	L-N: 500V/ LN-E: 1000V		
	Standby Power	0W		
	Start Time	<0.5s		
	Flickering %	<3%		
	Protection class	Class II		
Optical / Photometric	Rated lumens	Maintained/ Non-Maintained: AC 150lm, DC 150lm		
	Beam angle	76x38°		
	ССТ (К)	6500K		
	CRI	>80		
	SDCM	<6		
Lifetime	LED	SMD 2835, 16 pcs		
	Rated lifetime	30,000 hrs @ L70B50 55°C		
	Operating temperature	-0 to +40°C		
	Storage temperature	-10 to +70°C		
	Switching Cycle	30000 times		
	Over Temperature Protection	125°C		
	Storage Humidity	10% to 80% RH		
	Diffuser	UV stabilized polycarbonate clear		
	Body	ABS Base in white		
	Ingress protection	IP65		
Housing	Impact protection	IK08		
	Glow wire test: IEC 60598-2-22	850°C for gear tray/ diffuser, 650°C for base		
	Dimensions	351 x 111 x 63 mm		
	Weight	605g		
	Emergency Type	Maintained / Non-Maintained		
	Battery Type	3.6V 1500mAh Ni-Cd		
	Charging Time	24hrs		
Emergency	Charging Power	0.32W		
Mode	Operating Power in Emergency	1W		
	Output Current in Emergency	390mA		
	Duration time	180mins		
	Battery Certificates	Safety report Acc to IEC62133		
Application	Area	Indoor / Outdoor		
	Installation	Wall / Ceiling Mounting,		
		Recessed Bracket as accessory (steel in White)		
	Certifications	CB, ROHS		



## **Ordering Codes:**

Description	Shipping quantity	EAN10	EAN40	
LDVAL EM BLKHEAD 3W 3H IP65 10X1 ME LEDV	10	4058075562622	4058075562639	
LDVAL EM BLKHEAD RECESS KIT 10X1 MELEDV	10	4058075562646	4058075562653	

#### **Dimensions:**











Product Description	Length (mm)	Width (mm)	Height (mm)	Weight (g)
LDVAL EM BLKHEAD 3W 3H IP65	351	111	63	605
LDVAL EM BLKHEAD RECESS KIT	389	163	40	395