

DATA SHEET

LED EXIT LIGHT BLADE



Product Features

- 3 hours Self-contained Exit Light
- 4.2W
- 30Mtr. Viewing Distance
- Class II protection
- LED Indicator
- Maintained type.
- Wall/Surface Mount Installation, Suspend, Recessed, Flag Mount Installation possible with help of a mounting kit
- Battery type: LiFePO4 3.2V 1500mAh

Dimensions:



Product Description	Length	Width	Height	Weight
	(mm)	(mm)	(mm)	(g)
LDVAL EM BLADE 4.2W 30M 3H	310.5	36	210	610



General Specifications

LED EXIT LIGHT E	BLADE 4.2W 30M 3H			
Electrical Data	Wattage	4.2W		
	Voltage range	220 - 240VAC		
	Power factor	>0.5		
	Input current(max)	40mA		
	Line frequency	50/60Hz		
	Start Time	<1s		
	Protection class	Class II		
Optical / Photometric	Peak Luminous Intensity (Cd)	452Cd		
	Average Luminance (Cd/m2)	282Cd/m2		
	CRI	>70		
Other details	LED	SMD 2835 16pcs		
	Rated lifetime	36,000 hrs		
	Operating temperature	5 to +40°C		
	Storage temperature	5 to +70°C		
	Over Temperature Protection	125°C		
	Storage Humidity	< 70%		
	Ingress protection	IP20		
	Glow wire test: IEC 60598-2-22	850°C		
	Dimensions	310 x 36 x 210 mm		
	Weight	510g		
	Emergency Type	Self-Contained, Maintained		
	Battery Type	3.2V 1500mAh LiFePO4		
Emergency Mode	Charging Time	24hrs		
	Output Current in Emergency	420mA		
	Duration time	180mins		
	Battery Certificates	Safety report Acc to IEC62133		
Application	Area	Indoor		
	Installation	Wall/ Surface Mounting, recessed (with Kit), suspended (with Kit		
	Certifications	CB, RoHS		

Ordering Codes:

Description	Shipping quantity	EAN10	EAN40
LDVAL EM BLADE 4,2W 30M 3H 10X1 ME LEDV	10	4058075562684	4058075562691
LDVAL EM BLADE RECESS KIT ME LEDV	-	TBD	TBD
LDVAL EM BLADE FLAG KIT ME LEDV	-	TBD	TBD
LDVAL EM BLADE SUSP KIT ME LEDV	-	TBD	TBD



Mounting Options:































