

PRODUCT DATASHEET

OT 6/200...240/24 CE

Constant Voltage – Non dimmable | Constant Voltage – Non dimmable



Areas of application

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

Product benefits

- Installation in cold and hot environments
- Very stable output power
- High electronical reversible short-circuit, overload, overtemperature protection
- Independent installation possible

Product features

- Type of protection: IP20
- Wide operating temperature range: -20...+50 °C
- Lifetime: up to 50,000 h (temperature at max. t_c)

TECHNICAL DATA

Electrical data

Nominal wattage	8.30 W
Nominal output power	6 W ¹⁾
Nominal voltage	200...240 V
Nominal output voltage	24 V ²⁾
Input voltage AC	180...264 V ³⁾
U-OUT (working voltage)	25 V
Nominal current	0.08 A
Inrush current	15 A
Mains frequency	50/60 Hz
Total harmonic distortion	< 20 %
Power factor λ	0.50 ⁴⁾
ECG efficiency	80 %
Device power loss	1.5 W ⁵⁾
Max. ECG no. on circuit breaker 10 A (B)	30
Max. ECG no. on circuit breaker 16 A (B)	48
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L-N)	1 kV
Galvanic isolation	SELV

1) Partial load 0.9...6 W

2) ± 0.8 V

3) Permitted voltage range

4) Minimum

5) Maximum at 230 VAC, P_{out} =maximum, T_a =25 °C, steady state

Dimensions & Weight

Length	51.00 mm
Width	50.00 mm
Height	22.00 mm
Cable cross-section, input side	1 mm ²
Cable cross-section, output side	1 mm ²
Wire preparation length, input side	10 mm
Wire preparation length, output side	10 mm
Product weight	52.00 g

Colors & materials

Casing material	Plastic
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	70 °C
Max.housing temperature in case of fault	100 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h ¹⁾
--------------	-----------------------

¹⁾ At T_{case} = 60°C at T_c point / 10% failure rate

Additional product data

Encapsulated	No
--------------	----

Capabilities

Dimmable	No
Overheating protection	Automatic reversible
Overload protection	Automatic switch off, reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Max. cable length to lamp/LED module	10 m
Suitable for fixtures with prot. class	II

Certificates & Standards

Approval marks – approval	CE / VDE / ENEC 10 / CB
Standards	Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to EN 55015 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 61547
Protection class	II
Type of protection	IP65

LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

ADDITIONAL PRODUCT INFORMATION

- EMI pass verified with wire length of 2 m, from the ECG to the LED module at full load.
- Wiring longer than 2 m from ECG to LED module is possible, but site installation conditions may interfere with EMI with these longer cables. EMI is therefore not verified in this condition.
- For wires longer than 2 m, the appropriate cable cross section must be carefully selected to reduce voltage drop.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	OPTOTRONIC CONSTANT VOLTAGE
	Declarations of conformity	EU Declaration of Conformity 3578669
	Declarations of conformity	334859_Declaration of conformity – OT 6/200-240/10 CE
	Certificates	VDE ENEC Certificate 40038447
CAD/BIM files		Document name
	CAD data 3D PDF	313405_51x52x22 9900045

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321113269	Unpacked 1		52.00 g	
4008321113276	Shipping box 20	328 mm x 76 mm x 138 mm	1179.00 g	3.44 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.